


Núdzové svietidlo určené pre veľké výšky

Alfalux High Bay LED



Rozmery



L (mm)	W (mm)	D (mm)
400	136	95



Núdzové svietidlo určené pre osvetlenie priestorov s vysokou montážnou výškou svietidiel.

Umožňuje montáž až do 20m výšok.

60 000 h životnosť LED

Anti-vandal odolná konštrukcia Ip65

Svetelný zdroj

- 13W high power LED

Materiál

- Telo - hliník, biela povrchová úprava
- Kryt - číry polykarbonát
- Batéria - NiCd

Montáž

- Navrhnuté pre stropnú prisadenú montáž
- Montážne výšky 6 - 25m
- Trvalo / netrvalo svietiace
- CEAG verzie

Photometric Data

Mode	Mounting height (m)	Lux level directly under	1 lux min				0.5 lux min			
			⌈	⌋	⌈	⌋	⌈	⌋	⌈	⌋
Mtd/NMtd High Bay	6	-	3.5	8.2	12.2	5.8	3.7	7.3	11.6	6.1
	8	-	3.9	9.4	15.7	7	4.5	9.5	14.5	7.1
	10	-	4.1	10.5	18.3	7.5	5	11	17.3	7.9
	15	-	1.6	10.6	21.2	6.8	5.8	14.1	30	10
	20	-	-	-	-	-	3.2	14.6	30	10
230V Slave & CEAG High Bay	6	-	4.1	9.2	12.9	6.1	4.1	8.2	11.5	6.1
	10	-	5.2	12.3	19.7	8.8	5.6	12.3	17.8	8.6
	15	-	5.6	15	25.4	9.8	6.9	15.5	24	10.2
	20	-	3	15.1	27	7	6.5	15.7	30.3	11.7
	25	-	-	-	-	-	3.5	17	37.5	13.5
Mtd/NMtd Mid Bay	2.5	-	4.3	9.4	9.4	1.7	5.3	10.5	10.5	1.7
	2.8	-	3.3	9.3	9.3	1.4	5.7	11.5	11.5	1.4
	3.0	-	3.2	3.2	9.2	1.2	5.9	12.2	12.2	1.2
	4.0	-	-	-	-	-	4.9	12.5	12.5	0.67
230V Slave & CEAG Mid Bay	2.5	-	4.0	8.1	8.1	4.0	4.3	7.9	7.9	4.3
	2.8	-	4.4	9.0	9.0	4.4	4.7	8.6	8.6	4.7
	3.0	-	4.4	9.0	9.0	4.4	4.7	8.6	8.6	4.7
	4.0	-	5.9	12.4	12.4	5.9	6.1	11.6	11.6	6.1
	6.0	-	7.5	17.3	17.3	7.5	8.2	16.6	16.6	8.2
Self Contained 8W T5 NMtd	4.0	-	3.4	9.4	8.0	2.8	2.8	6.3	9.2	2.6
	6.0	-	3.2	9.8	8.0	2.8	2.6	11.9	10.6	2.1
	8.0	-	1.4	8.6	7.9	1.4	2.1	12.1	10.6	2.0
Mtd Self Contained 8W T5	10.0	-	-	-	-	-	2.0	12.9	10.6	1.6
	4.0	-	2.9	8.6	7.2	1.6	2.2	8.8	8.1	2.1
	6.0	-	2.2	9.2	7.6	2.2	2.1	10.6	8.7	2.1
	8.0	-	1.0	7.7	7.6	1.0	1.9	11.2	9.3	1.8
10.0	-	-	-	-	-	0.7	11.6	9.8	0.4	

Objednávacie kódy

System Mode	Cat No	Váha (kg)
LED Maintained 3Hr (Hi Bay)	HLLLEDH3H	2.7
LED Maintained 3Hr Intellem self-test (Hi Bay)	HLLLEDH3HIS	2.7
LED Maintained 3Hr EasiCheck 2 (Hi Bay)	HLLLEDH3HEC2	2.7
LED 230V AC Mains slave (Hi Bay)	HLLLEDH230	2.7
LED 230V Mains slave EasiCheck (Hi Bay)	HLLLEDH230EC	2.7
LED 230V CEAG slave (Hi Bay)	HLLLEDH230CG	2.7
LED Maintained 3Hr (Mid Bay)	HLLLEDL3H	2.7
LED Maintained 3Hr Intellem self-test (Mid Bay)	HLLLEDL3HIS	2.7
LED Maintained 3Hr EasiCheck 2 (Mid Bay)	HLLLEDL3HEC2	2.7
LED 230V AC Mains slave (Mid Bay)	HLLLEDL230	2.5
LED 230V Mains slave EasiCheck (Mid Bay)	HLLLEDL230EC	2.5
LED 230V CEAG slave (Mid Bay)	HLLLEDL230CG	2.5